



1. P.E. CELL, IF REQUIRED
2. DECORATIVE COOPER LIGHT FIXTURE UTD15SPW554 W/LAMP MINIMUM 150 WATT, H.P.S. (250 WATT AT CUL-DE-SAC)
3. POLE: SUN VALLEY 17-1060-14PT
FLUTED STRAIGHT 4" SHAFT W/3" TENON
TEMPLATE BASE PLATE W/12" BOLT CIRCLE
4. MANHOLE WITH ALUMINUM COVER
LOCATED FACING AWAY FROM CURB.
5. POLE FOUNDATION PER THE VILLAGE STANDARD
6. TOP OF FOUNDATION SHALL BE 1-1/2" ABOVE TOP OF CURB OR EDGE OF PAVEMENT UNLESS OTHERWISE APPROVED BY THE VILLAGE ENGINEER.



VILLAGE OF WHEELING
ENGINEERING DIVISION
2 COMMUNITY BOULEVARD
WHEELING, IL 60090
WWW.WHEELINGIL.GOV

DECORATIVE STREET LIGHT STANDARD

VILLAGE OF WHEELING SPECIFICATIONS AND DETAILS		REVISIONS	
FILE LOCATION		S.W.	03-06-02 AUTOCAD FILE
N:\ENGINEERING\STANDARDS\STREETLIGHTING		S.W.	05-21-02 REVISION
		K.R.G.	9-11-06 AUTOCAD FILE